AD-A089 581

MARK RESOURCES INC MARINA DEL REY CA
RECOMMENDATIONS FOR UPGRADING RFSS TO MEET NEAR-TERM REQUIREMEN-ETC(U)
JUL 78 R L MITCHELL

MRI-148-28

END
ONL
10-80
10-80
10-80
10-80
10-80
10-80
10-80
10-80
10-80
10-80





RFSS

RECOMMENDATIONS FOR UPGRADING RFSS TO MEET NEAR-TERM REQUIREMENTS

TECH NOTE 105-048

20 JUL 78

PREPARED FOR: RF SYSTEMS BRANCH (DRDMI-TDR)

SYSTEMS SIMULATION DIRECTORATE

TECHNOLOGY LABORATORY

US ARMY MIRADCOM REDSTONE ARSENAL, AL 35809

DAAK 40 - 76-6-0031

DISTRIBUTION STATEMENT A

Approved for public release; Distribution Unlimited

DR. R. L. MITCHELL MARK RESOURCES, INC. PREPARED BY:

4676 ADMIRALTY WAY

SUITE 303

MARINA DEL REY, CA 90291

DOC FILE COPY

80 9 22 134



RECOMMENDATIONS FOR UPGRADING RESS TO MEET

NEAR-TERM REQUIREMENTS.

R. L./Mitchell/

20 Jule 78

MRI 148-28

-148-28, MRI-TN-145-448

After reviewing the plans for the near term it appears that several more taps are going to be required for the rapped-delay line modulator. To accommodate a range resolution of .02 psec (10 ft) we must space the taps by .01 psec (5 ft) for the extended target simulation. If the target is 60 ft in length, it will encompass 12 taps plus about 4 more for "end effects". It is therefore recommended that the tapped-delay line modulator be extended to 16 taps. No additional digital processing hardware would be required for extended targets.

For clutter we would require 32 taps and modulators on 3 channels if the clutter were independent from range gate to range gate. However, additional processing hardware would be required to generate the modulation signals, namely several (> 4) AP120B's. It is therefore recommended that a simpler form of clutter be implemented that is consistent with the hardware for the extended target simulation.

miero

(ajyordinately

Anneenton For

Ports and
Transport

Transpo

1. TN-105-629

Distr. PANEL

APPLICATION OF

A special

391766

1676 ADMIRALTY WAY / SUITE 303 / MARINA DEL REY, CALIFORNIA 90291 / (213) 822-4955 🖋